

MULTI PALMSENS 4™

multi-channel
potentiostat / galvanostat / impedance analyzer



Contents

Contents	2
MultiPalmSens4: Highly Configurable	3
Supported Techniques	4
Measurement Specifications	5
System Channel Specifications.....	6
EIS Contour Accuracy Plot.....	8
Optional BiPotentiostat Specifications.....	9
Optional iR Compensation Module Specifications	9
Standard MultiPalmSens4 Kit	10
MultiPalmSens4 Accessories	11
MultiTrace: Software for Windows	13
Share the MultiPalmSens4 in the Local Area Network	15
Integrate Electrochemistry into Your Own Applications	17

➤ See for more information:
www.palmsens.com/mps4

MultiPalmSens4: Highly Configurable

The MultiPalmSens4 is a flexible multi-channel potentiostat, galvanostat and impedance analyzer which you can tailor to your requirements and budget.



Each channel can be configured with:

- ± 5 V or ± 10 V maximum potential range
- EIS/FRA with maximum frequency of 100 kHz or 1 MHz
- BiPotentiostat for second WE
- iR-compensation
- Galvanic Channel Isolation

More information on page 10

The MultiTrace software allows for using each channel individually or simultaneously or running a sequence of automated tasks on each channel. Each channel provides an additional auxiliary port for controlling peripherals or monitoring temperature or other analog signals.



Always a backup

Every channel of the MultiPalmSens4 is equipped with internal storage of 16 GB. This means all your measurements¹ can automatically be saved on board as backup. Measurements can be browsed and transferred to the PC easily using the MultiTrace software for Windows.

¹ Not supported for internal storage: EIS, Multistep and Mixed Mode

	ALL	CH1	CH2	CH3	CH4	CH5	CH6
Potential Range	10V	10V	10V	10V	5V	5V	5
Max. freq. for EIS	NO EIS	1MHz	1MHz	1MHz	100kHz	100kHz	1
BiPot	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IR-compensation	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Galvanically Isolated	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

➤ Configure your ideal MultiPalmSens4:
www.palmsens.com/mps4

Supported Techniques

The MultiPalmSens4 supports the following techniques.






Synchronising channels in Synched mode.




By enabling synchronization of channels and adjusting the setup of your cables, you can use the MultiPalmSens4 as a polypotentiostat. This means you can use multiple working electrodes, one counter and one reference electrode in the same cell at the same time. Your working electrodes all perform the same measurement.

Techniques marked with an  can be used in Synched mode.

Voltammetric techniques





- | | | |
|----------------------------|-----|--|
| ▪ Linear Sweep Voltammetry | LSV |  |
| ▪ Cyclic Voltammetry | CV |  |
| ▪ Fast Cyclic Voltammetry | FCV | |
| ▪ AC Voltammetry | ACV |  |

Pulsed techniques




- | | | |
|----------------------------------|-----|---|
| ▪ Differential Pulse Voltammetry | DPV |  |
| ▪ Square Wave Voltammetry | SWV |  |
| ▪ Normal Pulse Voltammetry | NPV |  |

These methods can all be used in their stripping modes which are applied for (ultra-) trace analysis.

Amperometric techniques

- | | | |
|---|------|--|
| ▪ Chronoamperometry | CA |  |
| ▪ Zero Resistance Amperometry | ZRA | |
| ▪ Chronocoulometry | CC |  |
| ▪ Multistep Amperometry | MA | |
| ▪ Fast Amperometry | FAM | |
| ▪ Pulsed Amperometric Detection | PAD |  |
| ▪ Multiple-Pulse Amperometric Detection | MPAD |  |

Galvanostatic techniques

- | | | |
|---------------------------------|---------|--|
| ▪ Linear Sweep Potentiometry | LSP |  |
| ▪ Chronopotentiometry | CP |  |
| ▪ Multistep Potentiometry | MP | |
| ▪ Open Circuit Potentiometry | OCP | |
| ▪ Stripping Chronopotentiometry | SCP/PSA |  |

Other

- | | | |
|---|----------|--|
| ▪ Mixed Mode | MM | |
| ▪ Potentiostatic and Galvanostatic Impedance spectroscopy at fixed frequency or frequency scan vs | EIS/GEIS | |
| ○ fixed potential or fixed current | | |
| ○ scanning potential or scanning current | | |
| ○ time | | |

Measurement Specifications

The following table shows limits for some technique-specific parameters.

	Parameter	Min	Max
All techniques (unless otherwise specified)	▪ Conditioning time	0	1600 s
	▪ Deposition time	0	1600 s
	▪ Equilibration time	0	1600 s
	▪ Step potential	0.076 mV	250 mV
	▪ Pulse potential	0.076 mV	250 mV
	▪ N data points	3	1,000,000
▪ NPV ▪ DPV	▪ Scan rate	0.1 mV/s (76.3 μ V step)	100 mV/s (5 mV step)
	▪ Pulse time	10 ms	300 ms
▪ SWV	▪ Frequency	1 Hz	1250 Hz
▪ ACV	▪ Frequency	1 Hz	2000 Hz
▪ LSV	▪ Scan rate	0.01 mV/s (76.3 μ V step)	500 V/s (10 mV step)
▪ CV	▪ Scan rate	0.01 mV/s (76.3 μ V step)	500 V/s (200 mV step)
▪ FCV	▪ Scan rate	400 mV/s (76.3 μ V step)	500 V/s (10 mV step)
	▪ N averaged scans	2	255
	▪ N equilibration scans	1	255
▪ PAD	▪ Interval time	50 ms	300 s
	▪ Pulse time	1 ms	1 s
	▪ N data points	N/A	1,000,000 (> 100 days at 10 s interval)
▪ MPAD	▪ Pulse time	100 ms	2 s
	▪ Run time	1.2 s	100,000 s
	▪ N potential levels	3	3
▪ CA ▪ CP ▪ OCP	▪ Interval time	0.4 ms	300 s
	▪ Run time	1 ms	> year
▪ MM ▪ MA ▪ MP	▪ N cycles	1	20,000
	▪ N levels	1	255
	▪ Level switching overhead time	~80 ms (+ ~100 ms with HW sync)	N/A
▪ FAM	▪ Interval time	0.02 ms	1 s
	▪ Run time	1 ms	30 s
	▪ N data points	3	4000 for interval time < 0.2 ms

System Channel Specifications

General			
	config	PS4.F#.05	PS4.F#.10
▪ dc potential range		±5 V	±10 V
▪ compliance voltage		±10 V	
▪ maximum current		±30 mA (typical)	
▪ max. acquisition rate		150 000 points/s	
▪ channel to channel isolation (for G.I. option)		≥ 1 GΩ // ≤ 10 nF	

Potentiostat (controlled potential mode)	
▪ applied dc-potential resolution	76.3 μV (18-bit)
▪ applied potential accuracy	≤ 0.1% or ±1 mV offset
▪ current ranges	100 pA to 10 mA (9 ranges)
▪ measured current accuracy	< 0.2% of current ±10 pA ±0.1% of range
▪ measured current resolution	0.005% of current range (18-bit, 5 fA on 100 pA range) 0.0025% of 10 mA range

Galvanostat (controlled current mode)	
▪ current ranges	1 nA to 10 mA (8 ranges)
▪ applied dc-current	±6 x applied current range
▪ applied dc-current resolution	0.0076% of applied range (<10 mA) 0.0038% of 10 mA range
▪ applied dc-current accuracy	< 0.2% of current ±10 pA ±0.1% of range
▪ potential ranges	10 mV, 100 mV, 1 V
▪ measured dc-potential resolution	78 μV at ±10 V (1 V range, 18-bit) 7.8 μV at ±1 V (100 mV range) 0.78 μV at ±0.1 V (10 mV range)
▪ measured dc-potential accuracy	≤ 0.05% for E < 9 V, ≤ 0.2% for E ≥ 9 V or ±1 mV offset

FRA / EIS (impedance measurements)

config	PS4.F1.##	PS4.F2.##
▪ frequency range	10 μ Hz to 100 kHz	10 μ Hz to 1 MHz
▪ ac-amplitude range	1 mV to 0.25 V rms, or 0.7 V p-p	

GEIS (galvanostatic impedance measurements)

▪ frequency range	10 μ Hz to 100 kHz (all configurations)
▪ ac-amplitude range	0.001 * range to 0.4 * range rms (<10 mA) 0.001 * range to 0.2 * range rms (10 mA)

Electrometer

▪ electrometer amplifier input	> 1 T Ω // 10 pF
▪ bandwidth	1 MHz


Other

▪ electrode connections	2 mm banana pins for RE, WE, CE and GND
▪ housing	15 x 25 x 25 cm ³
▪ weight	~4 kg
▪ temperature range	0 $^{\circ}$ C to + 50 $^{\circ}$ C
▪ power supply	external 12 V AC/DC adapter
▪ communication	USB-B
▪ internal storage space	16 GB (or >200 million datapoints)

Auxiliary port (D-Sub 15)

▪ analog input	\pm 10 V, 18-bit
▪ analog output	0-10 V, 12-bit (1 k Ω output impedance)
▪ digital I/O	4x digital output (5 V) 1x digital input (5 V)
▪ i-out and E-out	raw output of current and potential E-out \pm 10 V (1 k Ω output impedance) i-out \pm 6 V (1 k Ω output impedance)
▪ power	5 V-output (max. 150 mA)

EIS Contour Accuracy Plot



Note

The accuracy contour plot was determined under lab conditions using the standard 1-meter cell cable and should be used for reference purposes. Please note that the true limits of an impedance measurement are influenced by all components in the system, e.g. cables, the environment, and the cell.

Optional BiPotentiostat Specifications



Each channel of the MultiPalmSens4 can be extended in-factory with a BiPotentiostat module for use with a second Working Electrode.

BiPotentiostat specifications	
▪ dc-potential range	±5 V
▪ dc-potential resolution	153 μ V (16-bit)
▪ dc-offset error	≤ 0.1%, ±1 mV offset
▪ accuracy	≤ 0.1%
▪ current ranges	100 pA to 10 mA (9 ranges)
▪ maximum measured current	$i(\text{WE1}) + i(\text{WE2}) < 30 \text{ mA}$
▪ current resolution	0.005% of current range (5 fA on 100 pA range) 0.0025% of 10mA range
▪ current accuracy	≤ 0.1% current, ±0.2% range
▪ connection	comes with a cell cable with an additional (yellow) connector for WE2
▪ supported techniques	<ul style="list-style-type: none"> ▪ Linear Sweep Voltammetry ▪ Cyclic Voltammetry ▪ Chronoamperometry ▪ Multistep Amperometry

Optional iR Compensation Module Specifications



Each channel of the MultiPalmSens4 can be extended in-factory with an iR Compensation add-on module.

iR Compensation module specifications	
▪ method used for iR-drop compensation	Positive Feedback
▪ resolution of MDAC used for correcting potential	16-bit
▪ max. compensated resistance	1 M Ω
▪ max. bandwidth with iR-drop compensation enabled	10 kHz

Standard MultiPalmSens4 Kit

A standard MultiPalmSens4 comes in a soft carrying case with:

- MultiPalmSens4
- 12V external power supply
- USB cable
- 1 meter cell cables with 2 mm banana pins
- 4 croc clips per cable
- PalmSens Dummy Cell

Also included:

- MultiTrace software (on USB stick)
- Manual (hardcopy)
- Quick Start document
- Calibration reports



PalmSens Dummy Cell

Each channel can be configured with the following options and corresponding product codes:

code:	MPS4.F#.05	MPS4.F#.10
Potential range	-5V to +5V	-10V to +10V

code:	MPS4.F0.##	MPS4.F1.##	MPS4.F2.##
EIS configuration	NO EIS	100 kHz	1 MHz

Optional:

- BiPotentiostat module
- iR Compensation module
- Galvanic Channel Isolation

Example: channel configuration **MPS4.F1.05** corresponds to max. 100 kHz for EIS with $\pm 5V$ potential range.

Example: channel configuration **MPS4.F2.10+BiPot** corresponds to max. 1 MHz for EIS with $\pm 10V$ potential range and a BiPotentiostat module.



Soft carrying case

➤ [Configure your ideal MultiPalmSens:](http://www.palmsens.com/mps4)
www.palmsens.com/mps4

MultiPalmSens4 Accessories

In-factory add-on modules



BiPotentiostat add-on module

The BiPotentiostat Module is an optional extension for the PalmSens4 and is for applications requiring control of two independent working electrodes. The module fits inside the PalmSens instrument. The PStTrace software supports this module for linear sweep, cyclic voltammetry and amperometric detection with two working electrodes.

See page 9 for BiPotentiostat specifications



iR Compensation add-on module

The iR Compensation module is an optional extension for the PalmSens4. The resistance between the reference electrode and the double layer of the specimen can cause a significant potential drop, decreasing the applied potential where it is required. The module provides positive feedback to compensate for the iR-drop between Reference electrode and the outside of the double layer of the electrochemical cell.

See page 9 for iR Compensation module specifications

Other accessories



MUX8-R2 or MUX16 multiplexer

The MUX8-R2 is an 8-channel multiplexer. It allows the PalmSens4 to measure up to 8 cells, switching RE, CE, WE1 and WE2 or Sense.

In 8-WE mode it can measure up to eight working electrodes on sensor arrays with shared reference and counter electrodes as well. The MUX8-R2 is stackable up to 128 channels.



Magnetic stirrer with switch dongle

The magnetic stirrer controlled by the instrument is ideal for stripping analysis applications. The stirrer is switched on during the conditioning and deposition stages by means of the switch dongle.



LM35/TMP36 temperature sensor

This temperature sensor allows for monitoring of temperature during an experiment.

Two point calibration allows the user to precisely calibrate the sensor for the required temperature range. The calibration curve shows a linear slope of +10 mV/°C with 0.5°C Ensured Accuracy (at 25°C). It is rated for full 2°C to 150°C range (LM35) or -40°C to 125°C range (TMP36). The sensor has low self-heating (0.08°C in still air).



Differential Electrometer Amplifier (DEA)


The PalmSens Differential Electrometer Amplifier (DEA) is a high impedance input amplifier. It can be used as a floating voltage amplifier with differential input and single output to the auxiliary port of PalmSens devices.

Default range is -10V to 10V (1x gain). Possible gains are: 2x, 5x, 10x, 20x, 50x and 100x.

➤ See for more information:
www.palmsens.com/accessories

MultiTrace: Software for Windows

The MultiPalmSens4 comes with MultiTrace for Windows. MultiTrace allows the instrument to be controlled in two different modes: Individual and Simultaneous channel control mode. This mode can be selected when in the opening screen of MultiTrace.




Individual Mode: where each channel can run a measurement or script independently from the other channels.

Simultaneous Mode: where all channels run the same measurement.

Individual Mode

The individual mode gives an overview of all channels. Each channel can be selected separately and can run a measurement independently in parallel with other channels.

You can also run a script for a sequence of measurements and other actions on each channel.




Multiplexing each channel

Each MultiPalmSens4 channel can be extended with a MUX8-R2 multiplexer to connect eight individual cells (each with their own RE, CE and WE) to a single channel. This allows a fully equipped MultiPalmSens4 to work with 80 channels in total. You can stack multiple MUX8-R2 multiplexers for even more channels.

Each multiplexer connected to a channel of the MultiPalmSens4 is configurable in MultiTrace. See for more information:

www.palmsens.com/mux8-r2





Scripting

The individual mode also supports the option to run a sequence of measurements on a specific channel by using Scripting. Such a sequence can include different techniques and provides control commands for manual cell control or digital input or output lines.

Simultaneous Mode


In the Simultaneous Mode the MultiPalmSens4 works with all channels running the same measurement in parallel at the same time.


There is only one active method in the Method Editor which is started on all selected channels simultaneously upon start. All results are presented as overlays in the same plot.



This panel in the main screen contains a toggle button for each channel determines which channels are participating in the measurement.

Pop-up window shown when clicking a Curve in the legend.






Combining different instruments

MultiTrace supports all instrument models provided by PalmSens BV. A collection of different instruments can be combined for control by MultiTrace in both Individual and Simultaneous mode. Either multiple multi-channel or single-channel instruments can be combined.


Scripting

The intuitive script editor allows for easily creating a sequence of measurements or other tasks, by means of dragging and dropping actions in a list.



Other functions in MultiTrace

- Equivalent Circuit Fitting
- Advanced peak search algorithms
- Scripting (on each channel)
- Automatic data saving
- Open your data in Origin and Excel with one click of a button
- Save all available curves, measurement data and methods to a single file
- Direct feedback on validity of method parameters



Integration with third party software:

- Excel
- Origin
- Matlab
- ZView




Minimum System Requirements

- Windows 7, 8, 10 or 11
- 1 GHz or faster 32-bit (x86) or 64-bit (x64) processor
- 2 GB RAM (32-bit) or 4 GB RAM (64-bit)
- Screen resolution of 1280 x 800 pixels

➤ See for more information:
www.palmsens.com/multitrace

Share the MultiPalmSens4 in the Local Area Network

The Lablink Hub acts as the bridge between your MultiPalmSens4 and the network, allowing multiple users to work with the multi-channel instrument simultaneously.



➤ See for more information:
www.palmsens.com/lablink

Integrate Electrochemistry into Your Own Applications

Seamless Instrument Control

- Access all PalmSens potentiostats (single- and multi-channel) through our SDKs.
- Full control of measurement techniques, data acquisition, and real-time analysis.

Cross-Platform Support

- **Python SDK**
Script and automate experiments across platforms.
- **Windows .NET SDK**
Easily integrate in C#, VB.NET, or any .NET language.
- **Android & iOS SDKs**
Build mobile apps to run PalmSens instruments in the field.
- **LabVIEW & MATLAB examples**
Quick start for engineers and researchers.



Accelerate Development

- Pre-built code sample
- Clear documentation & active support
- Sample apps to get started within minutes



PalmSens SDKs
put you in control
from the lab to the field



➤ See for more information:
www.palmsens.com/dev

PalmSens BV has more than 50 distributors around the world.
Please contact us at info@palmstens.com or go to our website to get
in touch with a distributor in your region.



Please do not hesitate to contact PalmSens for more details: info@palmstens.com

PalmSens BV
The Netherlands
www.palmstens.com

DISCLAIMER

Changes in specifications and typing errors reserved.
Every effort has been made to ensure the accuracy of
this document. However, no rights can be claimed by
the contents of this document.

